

501P1925US00

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

APPLICANT : Shigeo Matsumoto et al.

APPLICATION No. : 09/993,094

FILING DATE : November 6, 2001

Group Art Unit : 2841

Examiner : VU, PHUONG T

TITLE : Adapter Device, Memory Device and Integrated Circuit Chip

Hon. Commissioner of Patents and Trademarks,  
Washington, D.C. 20231

SIR:

CERTIFIED TRANSLATION

I, Takashi Narita, am an official translator of the Japanese language into the English language and I hereby certify that the attached comprises an accurate translation into English of Japanese Application No. 2001-091268, filed on March 27, 2001.

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

September 21, 2005

Date

Takashi Narita

Takashi Narita

[Document Name] Patent Application

[Reference Number] 0100036203

[Filing Date] March 27, 2001

[To] Hon.Commissioner, Patent Office

[IPC] G11C 25/00

[Inventor]

[Address] c/o Sony Corporation  
7-35, Kitashinagawa 6-chome, Shinagawa-ku, Tokyo, Japan

[Name] Yasushi Fujita

[Inventor]

[Address] c/o Sony Corporation  
7-35, Kitashinagawa 6-chome, Shinagawa-ku, Tokyo, Japan

[Name] Shigeo Matsumoto

[Inventor]

[Address] c/o Sony Corporation  
7-35, Kitashinagawa 6-chome, Shinagawa-ku, Tokyo, Japan

[Name] Katsumi Endou

[Patent Applicant]

[Identification Number] 000002185

[Name] Sony Corporation

[Patent Attorney]

[Identification Number] 100067736

[Patent Attorney]

[Name] Akira Koike

[Patent Attorney]

[Identification Number] 100086335

[Patent Attorney]

[Name] Eiichi Tamura

[Patent Attorney]

[Identification Number] 100096677

[Patent Attorney]

[Name] Seiji Iga

[Priority Right based on a Prior Application]

[Application Number] P2000-344453

[Date of Application] November 10, 2000

[Indication of Charge]

[Number of Prepaid Ledger] 019530

[Amount] 21,000 yen

[List of Document]

[Document]	Specification	1
------------	---------------	---

[Document]	Drawing	1
------------	---------	---

[Document]	Summary	1
------------	---------	---

[General Power of Attorney Number]	9707387
------------------------------------	---------

[Need of Proof] Yes

[Name of Document] SPECIFICATION

[Title of the Invention]

Adapter Device, Memory Device and Integrated Circuit Chip

[Claims]

[Claim 1]

An adapter device comprising:

a substantially rectangular main body unit loaded on a host apparatus;

a first connection terminal provided to one side of said main body unit for electrical connection to said host apparatus;

one or a plurality of loading section(s) provided in succession to an inserting opening which is formed in the opposite side of said main body unit and into which is introduced an integrated circuit chip adapted for enclosing an integrated circuit device therein, said integrated circuit chip being loaded in said loading section(s);

a second connection terminal provided to said loading section(s) for electrical connection to a set of terminals provided to said integrated circuit chip; and

a controller enclosed in said main body unit and configured to control said integrated circuit chip loaded on said loading section(s).

[Claim 2]

A memory device comprising:

a substantially rectangular main body unit loaded on a host apparatus;

one or a plurality of memory chips each including a memory device therein;

a first connection terminal provided to one side of said main body unit for electrical connection to said host apparatus;

one or a plurality of loading sections provided in succession to an inserting opening which is formed in the opposite side of said main body unit and into which is introduced said memory chip(s), said memory chip(s) being loaded in said loading section(s);

a second connection terminal provided to said loading section(s) for electrical connection to a set of terminals provided to said memory chip; and

a controller enclosed in said main body unit for controlling the writing and readout of information signals to or from said one or plural memory chip(s) loaded in said loading section(s).

[Claim 3]

The memory device according to claim 2 wherein the main body unit has a size of a short side of approximately 21.45 mm, a size of a long side of approximately 50 mm and a size of a thickness of approximately 2.8 mm.

[Claim 4]

The memory device according to claim 2 wherein a further chip of the same shape as said memory chip may be loaded in said loading section(s) of said main body unit, said further chip having enclosed therein an integrated circuit device forming a logical circuit.

[Claim 5]

The memory device according to claim 2 wherein said memory device is a flash memory.

[Claim 6]

An integrated circuit chip inserted into and ejected from a substantially rectangular main body unit, loaded in a host apparatus, said integrated circuit chip having enclosed therein an integrated circuit device controlled by a controller enclosed in said main body unit, comprising:

a main chip body unit having said integrated circuit device enclosed therein and adapted for being inserted into and ejected from a loading section provided to said main body unit; and

a set of terminals provided to one side of said main chip body unit and adapted for being connected to connection terminals provided to said loading section to exchange information signals between said controller and the integrated circuit device.

[Claim 7]

The integrated circuit chip according to claim 6 wherein said integrated circuit device is a flash memory.

[Claim 8]

The integrated circuit chip according to claim 6 wherein said integrated circuit device is a logical circuit chip.

[Detailed Description of the Invention]

[0001]

#### [Technical Field of the Invention]

This invention relates to an adapter device to or from which an integrated circuit unit, such as memory chip, can be mounted or dismounted, and which is loaded on a host equipment as the integrated circuit unit is loaded thereon, a memory device comprised of the adapted device on which the memory chip is loaded, and to an integrated circuit chip that can be mounted or dismounted to or from the adapter device.

[0002]

#### [Prior Art]

As external memory device for an information processing apparatus, such as a personal computer or a digital still camera, there is a substantially plate-shaped memory device employing a semiconductor memory as a recording medium. The memory device of a larger storage capacity is able to store information signals up to a higher value of approximately 64 Mbytes.

[0003]

#### [Problems to be Solved by the Invention]

If this memory device is used as an external storage device, such as a digital still camera, picture data having a larger data size is manipulated. Since these numerous picture data cannot be stored in a sole memory device, the user has to purchase a new memory device.

[0004]

There are occasions where music air data or data processed by a computer are stored on this memory device in addition to the picture data. If many sorts of data are stored in a sole memory device, it may be an occurrence that the user forgets data stored on the memory device, with the result that data management becomes complex in order to prevent this from occurring.

[0005]

Moreover, in saving digital contents, protected by the copyright, such as music air data, in the memory device, a copyright management function needs to be provided in order to prohibit unauthorized copying of digital contents. Thus, in the memory device, it may become necessary to add a function capable of coping with different sorts of information signals to be saved.

[0006]

It is therefore an object of the present invention to provide a novel adapter device in which, by mounting an integrated circuit chip having variegated functions on a main body unit of the adapter device and by enabling the main body unit carrying the integrated circuit chip to be mounted on a host equipment, it is possible to add a variety of functions to a host equipment to improve convenience in use thereof.

[0007]

It is another object of the present invention to provide a novel memory device in which a memory chip can be mounted on or dismounted from the main body unit of the device to enable the storage capacity to be varied depending on the objective of



using the memory device by the user to improve convenience in use of the memory device.

[0008]

It is still another object of the present invention to provide a novel memory device in which a chip with a built-in integrated circuit unit having a function distinct from the memory function can be loaded on a loading portion of the memory chip to enable new functions to be added readily.

[0009]

It is yet another object of the present invention to provide an integrated circuit chip having a variety of functions for a main body unit of the adapter device that can be mounted to or dismounted from the host equipment and that is aimed at annexing a variety of functions to the host device.

[0010]

[Means to Solve the Problem]

According to the present invention, there is provided a an adapter device including: a substantially rectangular main body unit loaded on a host apparatus; a first connection terminal provided to one side of said main body unit for electrical connection to said host apparatus; one or a plurality of loading section(s) provided in succession to an inserting opening which is formed in the opposite side of said main body unit and into which is introduced an integrated circuit chip adapted for enclosing an integrated circuit device therein, said integrated circuit chip being loaded in said

loading section(s); a second connection terminal provided to said loading section(s) for electrical connection to a set of terminals provided to said integrated circuit chip; and a controller enclosed in said main body unit and configured to control said integrated circuit chip loaded on said loading section(s).

[0011]

According to the present invention, there is also provided a memory device including: a substantially rectangular main body unit loaded on a host apparatus; one or a plurality of memory chips each including a memory device therein; a first connection terminal provided to one side of said main body unit for electrical connection to said host apparatus; one or a plurality of loading sections provided in succession to an inserting opening which is formed in the opposite side of said main body unit and into which is introduced said memory chip(s), said memory chip(s) being loaded in said loading section(s); a second connection terminal provided to said loading section(s) for electrical connection to a set of terminals provided to said memory chip; and a controller enclosed in said main body unit for controlling the writing and readout of information signals to or from said one or plural memory chip(s) loaded in said loading section(s).

[0012]

According to the present invention, there is also provided an integrated circuit chip inserted into and ejected from a substantially rectangular main body unit, loaded in a host apparatus, said integrated circuit chip having enclosed therein an integrated

circuit device controlled by a controller enclosed in said main body unit, including: a main chip body unit having said integrated circuit device enclosed therein and adapted for being inserted into and ejected from a loading section provided to said main body unit; and a set of terminals provided to one side of said main chip body unit and adapted for being connected to connection terminals provided to said loading section to exchange information signals between said controller and the integrated circuit device.

[0013]

[Preferred Embodiment of the Invention]

Referring to the drawings, an adapter device, a memory device and an integrated circuit chip used as this memory device, according to the present invention, will be explained in detail.

[0014]

Referring to Fig.1, the memory device 10 is used as an external storage device for a host equipment 1, such as personal computer, a digital still camera, a digital video camera or an audio equipment. In this memory device 10, information signals, such as data processed by a computer, picture data, video data or music air data, are stored. The memory device 10 is loaded on the host equipment 1 through an insertion/ejection opening 2 provided in the host equipment 1, as shown in Fig.1, for recording and/or reproducing information signals.

[0015]

The memory device 10, used as described above, is in a substantially rectangular shape, with the length of a short side W1 being approximately 21.45 mm, a length of a long side W2 being approximately 50 mm and with the thickness W3 being 2.8 mm, as shown in Figs.2 and 5.

[0016]

This plate-shaped memory device 10 includes a casing 11, made up of an upper half 10a and a lower half 10b, forming the main body unit of the device, as shown in Figs.2 to 5. The upper half 10a and the lower half 10b, making up the casing 11, is formed by molding a rigid synthetic resin material. Within the casing 11, formed by bonding the upper half 10a and the lower half 10b, there is enclosed a semiconductor unit 12 operating as a controller for managing the writing and the readout of information signals. The casing 11 is formed to exhibit mechanical strength such that the casing 11 is not bent with a usual external force that may be applied during use to protect the internal semiconductor unit 12.

[0017]

On one short side of the casing 11 is formed a terminal unit 13 for extending from a front surface 11a to a bottom surface 11b. In this terminal unit 13, a number of engagement recesses 15 corresponding to the number of electrodes are formed by being delimited by partitioning walls 14. These engagement recesses 15 are engaged by terminals provided on the host equipment 1. A plural number of the electrodes 16, separated from one another by the partitioning walls 14, are provided on

the bottom surfaces of these engagement recesses 15. The electrodes 16, thus provided on the bottom surfaces of the engagement recesses 15, may be protected by the engagement recesses 15 from being directly touched by the user's hand or finger. The present casing 11 is provided with ten electrodes 16. Data exchange with the host equipment 1 is via the electrodes 16 provided in the terminal unit 13 over a serial interface. Specifically, the plural electrodes 16 are at least input terminals for serial protocol bus state signals BS, an input terminal for serial protocol data SDIO and an input terminal of serial clocks SCLK, in addition to a power source voltage VCC terminal and a reserve terminal.

[0018]

On one corner towards the front side 11a carrying the terminal unit 13 of the casing 11 is formed a chamfered portion 17 for allowing the user to discern the direction of insertion of the casing into the host equipment 1. In a lateral surface of the casing 11 in which is formed the chamfered portion 17, there is formed a mistaken insertion prohibiting groove 18 opened in the bottom surface 11b in continuation to the chamfered portion 17. When loading the memory device 10 on the host equipment 1, the chamfered portion 17 and the mistaken insertion prohibiting groove 18 control the direction of insertion of the memory device 10 into the host equipment 1 to prevent mistaken insertion. That is, if the memory device 10 has not been introduced in a regular condition via insertion/ejection opening 2, the chamfered portion 17 and the mistaken insertion prohibiting groove 18 prohibit the electrodes 16

and the set of terminals provided on the host equipment 1 from contacting the engagement recesses 15 delimited by the partitioning walls 14 to prevent the electrodes 16 from contacting the set of terminals provided on the host equipment 1.

[0019]

In one lateral surface 11c of the casing 11 towards its one front surface 11a is formed a detachment preventative recess 19 opened in the bottom surface 11b. When the casing 11 is inserted into the host equipment 1, the detachment preventative recess 19 is engaged with a resilient engagement piece provided on the host equipment 1 to prevent the detachment of the casing 11 from the host equipment 1. At a mid portion towards the other lateral surface 11d of the casing 11 is formed an engagement recess 21 opened in the bottom surface 11b. The engagement recess 21 is adapted for engaging with an ejection mechanism provided on the host equipment 1.

[0020]

Referring to Figs.2 and 6, three loading sections 22 are provided side-by-side along the length of the casing 11 for loading or unloading memory chips 27. These loading sections 22 are provided in continuation to insertion/ejection openings 23 formed in one lateral surface 11c of the casing 11. In a planar surface 11e of the casing 11 formed by the upper half 10a is formed an opening 24 through which the memory chips 27 can be inserted or ejected with the user's hand or finger. These loading sections 22 are formed to the same size as the memory chips 27, such that, when the memory chip 27 is loaded in position, the back surface 28e facing outwards

via insertion/ejection opening 23 of the memory chip 27 will be flush with the lateral surface 11c of the casing 11. By so doing, the back surface of the memory chip 27 is not protruded from the lateral surface 11c when the memory chip 27 is mounted on the loading section 22, with the result that insertion or ejection of the host equipment 1 may be performed smoothly with optimum hand feeling.

[0021]

The bottom surface 22a of the loading section 22 also operates as insertion or ejection guide in inserting or ejecting the memory chip 27. In the innermost part of the loading section 22, there are provided connection terminals 25 for establishing electrical connection with respect to the memory chip 27. In the lateral surface 22b in the loading section 22, parallel to the inserting direction of the memory chip 27, and in the lateral surface 22c thereof against which abuts the inserting end of the memory chip 27, there is formed a guide recess 26 for guiding the insertion or ejection of the memory chip 27 and for controlling its loading position.

[0022]

The memory chip 27, mounted on the loading section 22, includes a substantially rectangular main body unit of the chip 28 of substantially the same size as the loading section 22, molded of the same material as the casing 11, as shown in Fig.6. Within the main body unit of the chip 28 are enclosed one or more flash memories 29 as semiconductor memories. Each flash memory 29 has a storage capacity of, for example, 4 MB, 8 MB, 32 MB, 64 MB, 128 MB, ...

[0023]

On the bottom surface 28b towards the inserting end to the loading section 22 of the main body unit of the chip 28, that is towards its front side 28a, there are provided a plural number of terminals 31 electrically connected to the connection terminals 25 provided on the loading section 22. By these terminals 31 being electrically connected to the connection terminals 25 of the loading section 22, data can be written on or read out from the flash memory 29 by a control circuit provided in the semiconductor unit 12 provided on the casing 11.

[0024]

On a portion of the bottom surface 28b towards the front surface 28a of the main body unit of the chip 28 and towards both lateral surfaces 28c, 28d neighboring to the front surface 28a is protuberantly formed a guide section 32 adapted for guiding the insertion of the main body unit of the chip 28 into the loading section 22. This guide section 32 is engaged in the guide recess 26 formed in the loading section 22 to guide the insertion or ejection of the memory chip 27.

[0025]

In order to prevent detachment of the memory chip 27, mounted on the loading section 22, a detachment preventative member may be provided in the vicinity of the insertion/ejection openings 23. The number of the loading sections 22 may be one, two or not less than four instead of three.

[0026]



The circuit structure of the memory device 10 and the host equipment 1 on which the memory device 10 is mounted is now explained with reference to Fig.7.

[0027]

First, the circuit structure of the memory device 10 is explained. A controller 41, provided in the semiconductor unit 12 in the casing 11 of the memory device 10 includes a memory controller 42 for controlling data writing or readout to or from the flash memory 29 of the memory chip 27, a register 43 having a variety of parameters for data writing or readout, a page buffer 44 for transient data storage and a serial/parallel/serial interface (S/P-P/S interface) 45 for data exchange with the host equipment 1. The casing 11, forming the main body unit of the memory device 10, includes a chip interface 46 for data exchange between the flash memory 29 of the memory chip 27 and the controller 41 of the casing 11. The chip interface 46 enables data exchange between the controller 41 and a chip having a variety of functions when the chip is mounted on the loading section 22.

[0028]

The memory chip 27, mounted on or dismounted from the casing 11, includes a sole flash memory 29 and a chip interface 47 connected to the chip interface 46 to effect data exchange with the controller 41.

[0029]

By way of explaining the circuit structure of the host equipment 1, the host equipment 1 includes a file manager 51 performing file management of the memory

device 10, a transfer protocol interface 52 for executing access to a register 43 or to a page buffer 44 of the controller 41 of the memory device 10, and a serial interface 53 providing for the protocol necessary for data transfer over three signal lines, namely the serial clock SCLK, bus state BS and the serial data input/output SDIO. The file manager 51 is realized by a controller, such as CPU, of the host equipment 1 executing the application.

[0030]

By way of explaining the method of using the memory device 10, the memory chip 27 is inserted into the casing 11 via the insertion/ejection openings 23 provided in the lateral surface 11c of the casing 11, with the front surface 28a carrying the terminal 31 as the inserting end, as shown in Fig.6. At this time, the memory chip 27 is inserted into the loading section 22 via insertion/ejection openings 23 as the guide section 32 is engaged with the guide recess 26 formed in the loading section 22. Thus, the user is able to insert the memory chip 27 smoothly into the loading section 22. When the insertion of the memory chip 27 comes to a close, the chip interface 47 on the side memory chip 27 shown in Fig.7 is connected to the chip interface 46 on the casing 11.

[0031]

When the loading of the memory chip 27 on the loading section 22 comes to a close, the back surface 28e of the main body unit of the chip 28 forming the memory chip 27 is substantially flush with the lateral surface 11c of the casing 11 provided

with the insertion/ejection openings 23. Thus, the memory device 10 is able to insert the memory chip 27 smoothly into the host equipment 1. Moreover, the user may be safeguarded from having an objectionable touch feeling when holding the memory device 10 with his or her hand.

[0032]

It is unnecessary to have memory chips 27 mounted in all of the loading sections 22 provided in the casing 11, but only one or two memory chips 27 may suffice. Moreover, not only the memory chips 27 of the same storage capacity but also those having different storage capacities may be loaded. Therefore, the user is able to set the overall storage capacity of the memory device 10 depending on the use objects. Moreover, the user is able to load such memory chips 27, having stored therein data classified depending on data sorts, such as by loading a memory chip 27 having musical numbers stored therein, a memory chip 27 having picture data stored therein and a memory chip 27 having data for processing by a computer stored therein, or by loading a memory chip 27 having stored therein data in need of copyright management and a memory chip 27 having stored therein data not in need of copyright management. This enables the user to perform data management extremely readily.

[0033]

The memory chip 27 can be taken from the casing 11 extremely readily by sliding the memory chip 27, facing outwards via opening 24, towards the insertion/ejection openings 23.

[0034]

The memory device 10, in at least one of the loading sections 22 of which the memory chip 27 is loaded, is inserted via insertion/ejection opening 2 of the host equipment 1, with the front surface 11a carrying the terminal unit 13 of the casing 11 as an inserting end, as shown in Fig.1. It is noted that the chamfered portion 17 and the mistaken insertion prohibiting groove 18 are provided in the front surface 11a of the casing 11. Thus, if the memory device 10 is inserted via insertion/ejection opening 2 of the host equipment 1 under a non-usual condition, for example, in the upside-down condition, the memory device 10 cannot be inserted, thus prohibiting the mistaken insertion. If the memory device 10 is inserted into the loading section of the host equipment 1, the detachment preventative recess 19 formed in the memory device 10 is engaged by e.g., an elastic engagement portion provided on the loading section of the host equipment 1 to provide for positive mounting on the loading section to prevent inadvertent detachment.

[0035]

When the memory device 10 is loaded on the host equipment 1, the electrode 16 is caused to contact the set of terminals provided on the host equipment 1 so that the S/P·P/S interface 45 on the side memory device 10 is connected to a serial interface 53 on the host equipment 1, as shown in Fig.7. The S/P·P/S interface 45 then is fed from the host equipment 1 with the serial protocol bus state signals BS and serial clocks SCLK. The controller supervising the entire host equipment 1 executes the

application to realize the file manager 51 which then reads out the data information, such as filename or data size, from the flash memory 29 of the memory chip 27 loaded in the loading section 22 of the casing 11.

[0036]

When writing data in the flash memory 29 of the memory chip 27, the file manager 51 updates itself, at the same time as it outputs data to the memory device 10 through a transfer protocol interface 52 and a serial interface 53. Based on a control signals from the file manager 51, the memory controller 42 causes data input from the host equipment 1 to be transiently stored in a page buffer 44 through S/P-P/S interface 45 in accordance with the serial protocol bus state signals BS and the serial clocks SCLK. The memory controller 42 then causes data to be stored through the chip interfaces 46, 47 in the flash memory 29 of the memory chip 27 mounted in the loading section 22 of a preset address.

[0037]

When reading out data stored in the flash memory 29 of the memory chip 27 of a preset address, the memory controller 42 reads out data to the page buffer 44 from the flash memory 29 of the preset memory chip 27, in accordance with the serial protocol bus state signals BS and the serial clocks SCLK, to output the read-out data to the host equipment 1 through the S/P-P/S interface 45. The file manager 51 reads out data through the serial interface 53 and the transfer protocol interface 52.

[0038]

Meanwhile, the memory device 10, loaded on the loading section 22 of the host equipment 1, is ejected to outside via insertion/ejection opening 2 by an ejection mechanism engaged in the engagement recess 21 formed in the casing 11.

[0039]

Meanwhile, the memory chip 27 may be used by itself as an external storage device for the host equipment 1. At this time, the casing 11 forming the main body unit of the memory device 10 operates as an adapter device in reading out or writing data by a host equipment incapable of directly mounting the memory chip 27 on the loading section 22.

[0040]

With the above-described memory device 10, the overall storage capacity may be set solely by exchanging the memory chip 27. The user is able to change the entire storage capacity depending on the use object to improve convenience in use. The user is also able to put the memory device 10 to different uses from one loading section 22 to another. For example, the memory chip 27 mounted on the first loading section 22 may be used to store music airs, while the memory chip 27 mounted on the second loading section 22 may be used to store picture data and the memory chip 27 mounted on the third loading section 22 may be used to store processing data to be processed by a computer. So, the user may feel easy in supervising the data. Moreover, if a further memory is required, it is only sufficient if the user purchases only the memory chip 27 so that the user may be relieved of excess expenses.

[0041]

Meanwhile, an integrated circuit unit having a built-in logic circuit may be enclosed as an integrated circuit unit in the main body unit of the chip 28 in addition to the aforementioned flash memory 29.

[0042]

For example, in the embodiment shown in Fig.8, the memory chip 27 is mounted in each of the address 1 loading section 22 and address 2 loading section 22, whilst a copyright protection chip 61 is mounted on the address 3 loading section 22. If the memory chip 27 is mounted in each of the address 1 loading section 22 and address 2 loading section 22 and digital contents such as music air data or picture data of digital signals protected for copyrights are saved in these memory chips 27, it is necessary to protect e.g., the ID of the user in order to prevent illicit copying of the digital contents saved in these memory chips 27. Thus, in the present memory device, the user ID, for example, is stored in an address 3 in the main body unit of the chip 28 in the present memory device, whilst the copyright protection chip 61 having a built-in integrated circuit chip having a logic circuit capable of authentication mounted therein is mounted in the address 3 loading section 22. This gives a memory device having the function of protecting the copyrights.

[0043]

In the embodiment shown in Fig.9, the memory chip 27 is loaded on the address 1 loading section 22, the transmission/reception circuit chip 62 is mounted on the

address 2 loading section 22 and an antenna chip 63 is loaded on the address 3 loading section 22. This guarantees data transmission/reception between different memory devices.

[0044]

Of course, there is no particular limitation to the addresses of the loading sections 22 mounting these chips 27, 61, 62 or 63.

[0045]

With the memory device according to the present invention, as described above, since integrated circuit chips having a variety of functions may be loaded on the loading section 22 of the casing 11, a variety of functions may be annexed to the memory function with the use of the sole casing 11.

[0046]

According to the present invention, integrated circuit chips other than the memory chip 27 may be mounted on all of plural loading sections 22 provided on the casing 11 as an adapter device. The integrated circuit chips, other than the memory chip 27, mounted on the casing 11, as adapter device, operate as a function expanding device for the host equipment.

[0047]

[Effect of the Invention]

With the adapter device of the present invention, the functions owned by the integrated circuit chip can be annexed to those of the host equipment on exchanging



the integrated circuit chip mounted on the integrated circuit chip to improve the convenience in use of the host equipment.

[0048]

With the memory device of the present invention, since the overall storage capacity can be set solely by exchanging the memory chips, the user is able to change the storage capacity of the memory device depending on the use object to improve the convenience in use of the memory device. Moreover, the user is free to select the memory chip application from one loading section to another, with the result that the user is able to manage the data readily. In addition, if a further memory is required, the user only has to purchase a memory chip, and hence may be relieved of redundant economic loads.

[0049]

With the integrated circuit chip according to the present invention, new functions may readily be annexed to the host equipment simply by employing a memory device, a copyright protective circuit unit, a transmission/reception circuit unit, an antenna unit or a power source unit as the integrated circuit unit enclosed in the main body unit of the chip, and by mounting the adapter device carrying the integrated circuit chip to the host equipment. Moreover, by loading an integrated circuit chip having a function(s) other than the memory function to the adapter device, a variety of functions may be annexed to the memory device to enlarge the application of the memory device.

### [Brief Description of the Drawings]

Fig.1 illustrates the mode of using a memory device embodying the present invention.

Fig.2 is a plan view showing the memory device.

Fig.3 is a front view thereof.

Fig.4 is a bottom view thereof.

Fig.5 is a side view thereof.

Fig.6 is a perspective view for illustrating a memory chip that can be mounted on or dismounted from the memory device and a loading unit for loading the memory chip.

Fig.7 is a block diagram for illustrating a circuit structure of the memory device and the host equipment.

Fig.8 illustrates an instance of loading a memory chip and a copyright protection chip on a loading unit provided on a casing.


Fig.9 illustrates an instance of loading a memory chip, a transmission/reception circuit chip and an antenna chip.

### [Explanation of Referenced Numerals]


- 1 Host equipment
- 2 Insertion/ejection opening
- 10 Memory device
- 11 Casing

- 12 Semiconductor unit
- 13 Terminal unit
- 22 Loading sections
- 23 Insertion/ejection openings
- 24 Opening
- 25 Connection terminals
- 26 Guide recess
- 27 Memory chip
- 28 Chip
- 29 Flash memories
- 31 Terminals
- 32 Guide section


[DOCUMENT NAME] DRAWING  
[FIG.1]




[FIG.2]




[FIG.3]




[FIG.4]



[FIG.5]




[FIG.6]







[FIG.7]



[FIG.8]



[FIG.9]



[Name of Document] ABSTRACT

[Summary]

[Task]

A memory device having a variable storage capacity depending on the use object by a user to improve convenience in use of the device.

[Means for Solution]

The memory device 10 has a casing 11 mounted in a host equipment 1. The casing 11 has a plural number of loading sections 22 in or from each of which a memory chip 27 can be mounted or dismounted, respectively. The casing 11, carrying the memory chips, is inserted in an insertion opening 2 of the host equipment 1 with a terminal unit 13 as an inserting end. Data readout or writing from or into the memory chip 27 is controlled by a semiconductor unit 12 forming a control circuit enclosed in the casing 11. The memory device 10 may be of a recording capacity as desired by a user by changing the number of the memory chips 27 mounted on the loading sections 33 or by mounting memory chips 27 of variable recording capacities in the loading sections 22.

[Selected Drawing] FIG. 2